







SEND

AADL# W753





Discount is 10%

| | | Discount is 107 | • | Effective Oct | ober 1, 2023 | | | | |
|-------------------------|--------------------|---------------------------|--------------|---------------|--------------|--|--|--|--|
| | Client Information | | | | | | | | |
| | A A E D | • I : 1 : | P.O. #: | | | | | | |
| 一个数型 | IMEDI | n & bility_ | First Name: | | | | | | |
| | 5711- Ca | algary Trail NW | | | | | | | |
| All Trans | Edmonto | on AB T6H 2K1 | | | | | | | |
| | |)0 • F:780-430-9381 ¯ | | | | | | | |
| | AADL Vendor | # 0000612578-001 | Fax: | | | | | | |
| | Email address: | | | | | | | | |
| | | Order confirmation by | email | Yes 🗆 | No 🗆 | | | | |
| Price Specification | | Subscribe to Physipro™ | newsletter | Yes 🗆 | No 🗆 | | | | |
| Technical Specification | _ | Factory installation of p | ostural aids | Yes 🗆 | No 🗆 | | | | |

| 4 | | | | |
|--------------------------------|--|---------|----------------|---------------|
| | MODEL | | | |
| PRODUCT | DESCRIPTION | CODE | PRICE | CHOICE |
| Neox 4-wheel | 4-wheel tilt-in-space wheelchair - 45° For seat widths between 14" and 22". Maximum load capacity of 265 lbs. Tilting mechanism from -5° to 45°. Frame color: Silver | NGNX1 | \$2495 | |
| Neox 6-wheel | Mid-wheel drive option. Rear tilt mechanism option strongly recommended. A Not funded by AADL. | NGNX2TR | \$965 A | |
| | MAIN OPTIONS | | | |
| Tilt Mechanism | Anterior tilt locking collar Desired angle:° | NX82 | \$120 | □ ← |
| Power Tilt | Maximum tilt limited at 45° (Maximum weight capacity 265 lbs) | NGNXPWT | \$1700 | |
| | SEAT STRUCTURE | | | |
| Rigid seat plate | Rigid aluminium seat pan, adjustable in depth, with two 2-inch wide velcro "hook" strips. | NGNX5 | N/C | |
| | FIXED EFFECTIVE SEAT WIDTH | | | |
| Standard Frame (Max 265 lb) | 14" | NGNXQ | N/C | + |
| | OVERALL WIDTH (INFORMATION CHART) Spoke wheel: Seat width + 10 ¼" Mag wheel: Seat width + 11 ¼" | | | |
| | ADJUSTABLE EFFECTIVE SEAT DEPTH | | | |
| Standard Frame | 14" 🗆 15" 🗆 16" 🗆 17" 🗆 18" 🗆 | | N/C | + |
| Extended Frame | 19" 🗆 20" 🗆 | NGNXQ | \$205 | + |
| | 21" 🗆 22" 🗆 | | \$345 | ← |





4 WHEEL NEOX - SEAT-TO-FLOOR HEIGHT, CASTERS AND WHEELS

| SEAT-TO-FLOOR INFORMATION TABLE - (4 WHEEL MODEL) | | | | | | | | |
|---|------------------|-------------------------|--|--|--|--|--|--|
| PROPULSION & REAR WHEELS | CASTER WHEELS | SEAT-TO-FLOOR HEIGHT | | | | | | |
| | S5" | 13" to 18" | | | | | | |
| 12" | S6" | 14" to 19" | | | | | | |
| | S8" | 15" to 20" | | | | | | |
| 20" | S5", D5" | 13" to 18" | | | | | | |
| 20 | S6" | 13" to 18" | | | | | | |
| 22" | S6", D6" | 14" to 19" | | | | | | |
| 22 | S8" | 15" to 20" | | | | | | |
| 24" | S8", D6" | 15" to 20" | | | | | | |

| SEAT-TO-FLOOR HEIGHT - (4 WHEEL MODEL) | | | | | | | |
|--|---|----------|--|--|--|--|--|
| Please select | 13" | | | | | | |
| the desired | 14" | | | | | | |
| seat-to-floor | 15" | | | | | | |
| height. | 16" | | | | | | |
| | 17" | | | | | | |
| → | 18" | | | | | | |
| | 19" | | | | | | |
| | 20" | | | | | | |
| DEFINITION | | | | | | | |
| S5" - S6" - S8" | Standard Front Fork with height ad | justment | | | | | |
| D5" - D6" | Dynamic Front Fork with height adjustment | | | | | | |

| | C | ASTERS AND W | /HEELS (4-WHEI | EL MODEL) | | | |
|------------------------|--------------------|------------------------------|----------------|------------|---------|------------|----------|
| | | FRC | NT CASTERS | | | | |
| PRODUCT | | DESCRIPT | TION | | CODE | PRICE | CHOICE |
| Dynamic Front Forks | Dynamic forks with | n <mark>height</mark> adjusn | nents | | NXDYNFR | \$192 Pair | |
| Front Caster Tires | Polyurethane | 5" x 1½" □ | 6" x 1½" □ | 8" x 1½" □ | WHUN- | N/C | + |
| | | PROPI | JLSION WHEELS | | | | |
| Rims | Mag Wheel | | | | NX52MA | N/C | |
| Kiiiis | Spoke Wheel | | | | NX52SW | N/C | |
| | Diameter | 20" 🗆 | 22" 🗆 | 24" 🗆 | 1 | - | ← |
| Tires | Polyurethane | | NX53UR | N/C | | | |
| | Standard pressure | | NX53SP | \$80 Pair | | | |
| | Aluminium | | | | NX44 | N/C | |
| Handrims | Plastic Coated | | NX45 | \$130 Pair | | | |
| nanurims | ½-inch closer adju | - | - | | | | |
| | Omit (Reduce ove | rall width by 1 | 1/2") | | - | - | |
| Axles | Threaded Axles | | | | NGNX47 | N/C | |
| Axies | Quick-release Axle | ·S | NGNX48 | \$92 Pair | | | |
| | | REA | AR WHEELS | | | | |
| | Size | 12" | | | 1200 | N/C | |
| Rear wheels | Tires | Polyurethane | | | WHUN- | N/C | |
| | 11162 | Standard pres | ssure | | WHPG- | N/C | |





MID-WHEEL DRIVE OPTION - SEAT-TO-FLOOR HEIGHT, CASTERS AND WHEELS

| SEAT-TO-FLOOR INFORMATION TABLE - (6 WHEEL MODEL) | | | | | | | | |
|---|---|-------------------------|--|--|--|--|--|--|
| PROPULSION WHEELS | CASTER WHEELS | SEAT-TO-FLOOR HEIGHT | | | | | | |
| 20" | D5" | 13" to 18" | | | | | | |
| 22" | D6" | 14" to 19" | | | | | | |
| 24" | D6" | 15" to 20" | | | | | | |
| DEFINITION | | | | | | | | |
| D5" - D6" | Dynamic Front Fork with height adjustment | | | | | | | |

| SEAT-TO-FLOOR HEIGHT - (6 WHEEL MODEL) | | | | | | |
|---|-----|--|--|--|--|--|
| Please select the desired seat-to-floor | 13" | | | | | |
| | 14" | | | | | |
| | 15" | | | | | |
| height. | 16" | | | | | |
| | 17" | | | | | |
| → | 18" | | | | | |
| 7 | 19" | | | | | |
| | 20" | | | | | |

| | CASTERS AND WHEELS - (6 WHEEL MODEL) | | | | | | | | |
|-------------------------------|--|--------|------------|--------|--|--|--|--|--|
| Note | Front caster wheel size is determined during assembly according to the selected propulsion wheel diameter. | | | | | | | | |
| | PROPULSION WHEELS | | | | | | | | |
| PRODUCT | DESCRIPTION | CODE | PRICE | CHOICE | | | | | |
| Rims | Mag Wheel | NX52MA | N/C | | | | | | |
| Kiiiis | Spoke Wheel | NX52SW | N/C | | | | | | |
| | Diameter 20" ☐ 22" ☐ 24" ☐ | - | - | + | | | | | |
| Tires | Polyurethane | NX53UR | N/C | | | | | | |
| | Standard pressure | NX53SP | \$80 Pair | | | | | | |
| | Aluminium | NX44 | N/C | | | | | | |
| He add as | Plastic Coated | NX45 | \$130 Pair | | | | | | |
| Handrims | ½-inch closer adjustment (Reduce overall width by 1") | - | - | | | | | | |
| | Omit (Reduce overall width by 1 ½") | - | - | | | | | | |
| Avles | Threaded Axles | NGNX47 | N/C | | | | | | |
| Axles | Quick-release Axles | NGNX48 | \$92 Pair | | | | | | |
| | REAR CASTER TILT MECHANISM | | | | | | | | |
| Rear Caster Tilt Mechanism | Rear Caster tilt mechanism facilitates getting over obstacles or elevation changes. | NXTR | N/C | | | | | | |

| WHEEL LOCKS | | | | | | | | |
|-------------|--|---------|-----------|--|--|--|--|--|
| | Push to lock | NGNX29 | N/C | | | | | |
| Wheel locks | Pull to lock | NGNX55 | N/C | | | | | |
| | Attendant Wheel Lock (Foot Operated Brake) | NX32 | \$485 | | | | | |
| | Standard Wheel Lock Extension - 6" | NGNX30 | \$40 Pair | | | | | |
| Extensions | Telescopic Wheel Lock Extension - 6" | NGNX31 | \$60 Pair | | | | | |
| | ANTI-TIPS | | | | | | | |
| A . 11 T' | Al cold on all line to all the Containing | NGNX40A | N/C | | | | | |
| Anti-Tips | Aluminium anti-tips (available for 4 Wheel model only) | NGNX40B | | | | | | |





| | | | | BACK POS | STS | | | | | | | |
|-----------------------------------|---|--|--------------|-------------------|--------------|-------------|--------------|------------|----------|--|--|--|
| Notes | All back po | All back post are adjustable in angle and height by increments of 1". | | | | | | | | | | |
| PRODUCT | DESCRIPTION | | | | | | | PRICE | CHOICE | | | |
| Standard | Medium | 16" 🗆 | 17" 🗆 | 18" □ | 19" 🗆 | 20" 🗆 | NGNXH1620 | N/C | | | | |
| Back Posts (with grip handles) | Long | 21" 🗆 | 22" 🗆 | 23" 🗆 | 24" 🗆 | 25" 🗖 | NGNXH2125 | \$95 Pair | + | | | |
| Dynamic | Medium | 18" 🗆 | 19" 🗆 | 20" 🗆 | 21" 🗆 | 22" 🗆 | NCNIVOVALA | ĆEZE Dai: | + | | | |
| Back Posts | Long | 23" 🗆 | 24" 🗆 | 25" 🗆 | 26" 🗆 | 27" 🗆 | NGNXDYNA | \$575 Pair | | | | |
| | | | E | BACKREST : | ГҮРЕ | | | | | | | |
| s | RECLININ | G GAS SP | RING BAC | KREST: Cor | npatible wit | th the Stai | ndard back p | osts only. | | | | |
| Backrest Type | Reclining (| Gas Spring | Backrest (| 85° to 130' | °) 🔑 | | NGNXREC | \$1100 | | | | |
| | | | В | ACKREST A | NGLE | | | | | | | |
| ₽ . | 115°& 120° | BACKREST | ANGLES: No | ot compati | ble with Dy | namic Bac | ck posts. | | | | | |
| Backrest | Ajustable | _ | | | | 95° □ | | | _ | | | |
| Angle | 100° [| J 10! | 5° □ 11 | .0° □ 1 | 15° □ | 20° □ & | - | N/C | ← | | | |
| | | | | STROLLER | BAR | | | | | | | |
| Stroller Bar | Angle adj | ustable str | oller bar | | | | NGNX9 | N/C | | | | |
| | | | | ARMRES | T | | | | | | | |
| | "T" TYPE ARMREST: Removable armrests, adjustable in height by increments of ½", includes locking mechanism and clothing guards. Provides ½" clearance on each side. | | | | | | | | | | | |
| Notes | | | | | | | | each side. | | | | |
| | "T" TYPE ARMREST is strongly recommeded to optimize the tilt and Lowered: Adjustable from 6 ¾" to 10 ½" | | | | | | 08-TH1- | N/C | | | | |
| "T" Type | Standard: | | 08-TH2- | N/C | | | | | | | | |
| Armrest | Elevated: Adjustable from 10" to 14 ½" | | | | | | 08-TH3- | N/C | | | | |
| "T" Type | Foam Pad | - Desk len | gth (2 ¼" x | 10") | 1 | | FS | N/C | | | | |
| Armrest Pads | Foam Pad | - Full leng | th (2 ¼" x 1 | .4") | | | FL | N/C | | | | |
| Armrest Extension | 3" Armres | t pad exte | nsion | | | | PH-3046 | \$124 Pair | | | | |
| | | "U" TYPE ARMREST: Removable, flip-back armrests, adjustable in height by increments of ½", | | | | | | | | | | |
| Notes | includes locking mechanism and clothing guards. Provides ½" clearance on each side. "U" TYPE ARMREST: The "U" type armrest can significately limit tilt angle. | | | | | | | | | | | |
| Notes | | | | | | | | | | | | |
| | LOWERED | "U" TYPE A | RMREST: N | lot availab | le with a wh | neelchair c | onfigured at | | " depth. | | | |
| "U" Type | | | e from 6 ¾' | | | | NGNX11 | \$263 Pair | | | | |
| Armrest | | | e from 8 ½ | | | | NGNX10 | N/C | | | | |
| | | | e from 12" | | | | NGNXM13 | \$263 Pair | | | | |
| "U" Type | | | ght (2 ¼" x | | | | NGNX13 | N/C | | | | |
| Armrest Pads | | | ht (2 ¼" x 1 | .4") | | | NGNX12 | N/C | | | | |
| Armrest Extension | 3" Armres | t pad exte | nsion | | | | PH-3046 | \$124 Pair | | | | |





| | | | | F001 | REST | | | | | | | |
|-------------------------------|--|---|---------------------------------------|----------------|---------------|------------|-----------|-------------|------------|----------|--|--|
| Ness | | Footrest can be swivelled inwards or outwards, is removable and is equipped with a locking mechanism. Adjustable in lenght from 10 1/2" to 21" by increments of 1/2". | | | | | | | | | | |
| Note | Minimal lenght of the 60° footrest is 11 1/4". | | | | | | | | | | | |
| PRODUCT | IVIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII | CODE | PRICE | CHOICE | | | | | | | | |
| TROBUCT | | | | RIPTION 50° | | | | NGNX60 | N/C | | | |
| Footrest | | | | 70° | | | | NGNX70 | N/C | | | |
| Angle | | 90° | | | | | | | \$149 Pair | | | |
| | Small: | 10 1/2" t | | | | | | S | | | | |
| _ | Jillall. | | | length:_ | | " (| ± ¼") | 5 | | | | |
| Footrest Length | Medium: | | desired | length:_ | | " (| ± ¼") | M | N/C | ← | | |
| | Long: | 16" to 2 Specify | | length:_ | | " (| ± ¼") | L | | | | |
| | | ELE\ | /ATING | AND AR | TICULAT | TING LEC | GREST | | | | | |
| Note | The elevating a installed on the | | | | | | | mechanism a | and can be | | | |
| Flourations and | X-Small: | 12"□ | , , , , , , , , , , , , , , , , , , , | 13"[| | | "□ | NGNX65 | | | | |
| Elevating and Articulating | Small: | 14"□ | | 15" C |] | 16 | " " | NGNX15 | d= 4= 5 · | _ | | |
| Legrest | Medium: | 17"□ | | 18"[|] | 19 | " " | NGNX16 | \$545 Pair | + | | |
| Length | Long: | 20"□ | | 21"[|] | 22 | "□ | NGNX66 | | | | |
| | | | | CALF SU | PPORTS | | | | | | | |
| s | Calf support is | included | with th | e elevati | ng and a | articulati | ing legre | st. | | | | |
| Note | Calf support is | adjustab | le in hei | ght, dep | th and a | ngle. | | | | _ | | |
| Calf Supports | 6" x 8" - Flat Padding 🔑 | | | | | | NGNX18 | N/C | | | | |
| can supports | 6" x 8" - Profile | d Paddin | g 🤑 | | | | | NGNX20 | N/C | | | |
| | | | | FOOTE | PLATES | | | | | | | |
| Flip-Up | Aluminium footplates, 6" X 8" | | | | | | NX39 | N/C | | | | |
| Footplates | Aluminium foo | ' ' | | | | | | NX58 | N/C | | | |
| Flip-up & Adjustable | Aluminium foo | tplates w | ith angl | e and de | oth adjus | sments | X | NGNX27 | \$180 Pair | | | |
| Footplates | Size: | 6" X 6 ¾ | " | | | | | NGNAZA | 7100 T dii | | | |
| | Footplate | | | Seat \ | | | | | | | | |
| | Sizes | 14" | 15" | 16" | 17" | 18" | 19" + | | | | | |
| Oversized Flip-up | 5" x 9" | | ᄆ | | | <u> </u> | | | | | | |
| Footplate | 6" x 9" 6" x 10" | | | | | | | NGNXX | \$195 Pair | ← | | |
| with | 7" x 9" | _ | | | | | | | | | | |
| Angle and Depth Adjustment | 7" x 10" | | N/A | | | | | | | | | |
| Adjustment | 8" x 9" | N/A | | | | | | | | | | |
| | 8" x 10" | | | | | | | | | | | |
| One Piece | Aluminium foo | otplate w | ith angl | e and de | pth adju | ısments | | E\A/ | \$350 | | | |
| Flip-up Footplate | Depth: 6' | '□ 8' | '□ 1 | .0" 🗆 | | | | FW | | + | | |
| Heel Support Strap | Adjustable in le | ength | | | | | | NGNX28 | N/C | | | |






| | | PELV | IC POSITIONING | BELT | | | |
|----------------------------|--------------------------------------|---------------------------------------|----------------------------|-----------------------|----------------|------------|----------|
| PRODUCT | | DESC | RIPTION | | CODE | PRICE | CHOICE |
| Positioning Belt | Pelvic positioni | ng belt with au | to-style buckle, | 2" | NGNX41 | \$35 | |
| | | REFLEC | TIVE SAFETY ST | ICKERS | | | |
| Reflective safety stickers | Sticker pack inc 2 reflective red | | ve white stickers | s and | NGNX74 | \$12 | |
| | | ADAPTED TRA | NSPORT SECURI | EMENT POINTS | | | |
| Securement Points | 4 Tie-dowi Certified IS | n strap securem SO/DIS 7176-19 | nent points for a :2019 | dapted transport, | NGNX42 | N/C | |
| | | | GEN TANK HOL | | | | |
| Oxygen Tank Holder | | th size D and E or with the stroll | oxygen tanks on ler bar | ly | NX43 | \$180 | |
| | | | SEAT CUSHIONS | | | | |
| s | SEAT CUSHION Flat cut. | NS: The dimensi | on of the cushior | n will be adapted to | the size of th | ne wheelch | air. |
| Urethane & | Thickness of 2" | , flat | | | S3350 | \$126 | |
| Memory Foam | Thickness of 3" | , flat | | | S3350 | \$126 | |
| Cushions | Thickness of 4" | , flat | S3350 | \$126 | | | |
| | | | BACKRESTS | | | | |
| s | Backrests: For with an upchar | | or bariatric dime | nsions, please fill t | the Contour (| Cinch orde | form |
| | Rigid Backrest | (%-inch thick | ABS) | | NGNX8 | \$150 | |
| | Omit | | 70 | > | - | - | |
| Backrests | Contour Cinch | 16" x 18" □ | 16" x 20" □ | 18" x 18" □ | CINCH | N/C | ← |
| | Back | 18" x 20" □ | 20" x 18" □ | 20" x 20" □ | 0 | 11, 0 | _ |
| | | | TENSION BARS | | | | |
| | Standard Tensi | | | • | NGNX87 | N/C | |
| Tension Bars | 2-inch Deep Te | NGNXQ57 | N/C | | | | |
| | Tension Bar wit Mounting Fixtu | NGNXHSUP | \$94 | | | | |
| | | | HEADREST | | | | |
| Headrest | Multi-Adjustab | le Straight Head | drest Support | | NX34 | N/C | |
| Headlest | Standard Pads | 7" x 4" □ | 8" x 5" □ | 9" x 6" □ | NX36 | N/C | ← |





DETERMINATION OF TILT ANGLE ACCORDING TO THE CHOSEN WHEELCHAIR CONFIGURATIONS

| | | INCLINATION ANGLE (+/-1°) |
|---|----------|------------------------------|
| TILT MECHANISM POSITION (STFH) | 6 (13'') | 34° |
| | 6 (14'') | 39° |
| | 6 (15'') | 43° |
| | 5 (16'') | 45° |
| | 4 (17'') | 45° |
| | 3 (18'') | 45° |
| | 2 (19'') | 45° |
| | 1 (20'') | 45° |



Notes

The U-shaped armrest, the reclining backrest and the dynamic back posts can influence the results. The attendant wheel lock and an oxygen tank holder may also impact the tilt angle results.

The position number of the tilt mechanism can vary according to the selected propulsion wheel diameter.

Notes: